

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>30 SEP 2001</b>		2. REPORT TYPE		3. DATES COVERED <b>00-00-2001 to 00-00-2001</b>	
4. TITLE AND SUBTITLE <b>Dual-Beam Interferometer Development and Validation</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>Electrical &amp; Computer Engineering,,Knowles Engineering Bldg., Rm. 215,,University of Massachusetts,,Amherst,,MA,01003</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>3</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

## **Dual-Beam Interferometer Development and Validation**

Stephen Frasier

Electrical & Computer Engineering  
Knowles Engineering Bldg., Rm. 215

University of Massachusetts

Amherst, MA 01003

phone: (413) 545-4582 fax: (413) 545-4652 email: [frasier@ecs.umass.edu](mailto:frasier@ecs.umass.edu)

James Carswell

Electrical & Computer Engineering  
Knowles Engineering Bldg., Rm. 215

University of Massachusetts

Amherst, MA 01003

phone: (413) 545-4867 fax: (413) 545-4652 email: [carswell@mirsl.ecs.umass.edu](mailto:carswell@mirsl.ecs.umass.edu)

Grant Number: N00014-98-1-0612

<http://www.umass.edu/mirsl>

### **LONG-TERM GOALS**

My long-term goal is to contribute to our understanding of the upper ocean and lower atmosphere through the development and application of microwave, acoustic, and optical remote sensing techniques.

### **OBJECTIVES**

The objective of this effort is to develop an instrument and techniques to estimate surface current vectors from aircraft using along-track interferometry.

### **APPROACH**


Our approach is to design and develop a low-cost dual-beam interferometric radar termed the Dual-Beam Interferometer (DBI). The radar concept is that of an along-track interferometric SAR producing two beams, one squinted forward and one squinted aft. Such a concept was originally proposed by Rodriguez et al. (1995). The two interferometer beams yield two components of the surface Doppler velocity from which surface current is estimated. The instrument is to be packaged into a wing-mounted pod suitable for mounting on NOAA WP-3D research aircraft, or other aircraft with compatible mounting pylons. Testing of the instrument is planned in the context of NOAA/HRD's air-sea interaction experiments and other planned operations in 2002.

### **WORK COMPLETED**

Construction of the radar electronics was led by graduate student Juan Capdevila. An aircraft-quality instrument chassis has been designed and constructed. In October, it will be shipped to the pod manufacturer (Zivko Aeronautics) who will provide the shell.

## RESULTS

Figure 1 is a 3D CAD model of the instrument in the pod chassis (pod shell not shown). Most of the radar electronics are contained in the payload area located between supports for the microstrip patch array antennas. The baseline between antennas is approximately 1 m.



*Figure 1: 3D CAD model of the DBI instrument in the pod chassis (pod shell not shown).*

## IMPACT/APPLICATIONS

Along-track interferometric SARs commonly provide a single component of surface Doppler velocity. The ability to obtain surface velocity vector estimates in a single aircraft pass would permit long distance strip mapping of current vectors in, for example, coastal regions.

## TRANSITIONS

None.

## RELATED PROJECTS

Using the FOPAIR imaging radar developed at UMass, we are also investigating the utility of imaging Doppler radar for use in estimating currents and wave heights within and just beyond the surf zone.

## REFERENCES

Rodriguez, E., D. Imel, B. Houshmand, 1995: "Two Dimensional Surface Currents Using Vector Along-Track Interferometry", PIERS'95 Proceedings, Seattle, WA, p. 763.

## PUBLICATIONS

Frasier, S.J., and A.J. Camps, 2001: "Dual-Beam Interferometry for Ocean Surface Current Vector Mapping", *IEEE Trans. Geosci. & Rem. Sensing*, **39**(2), 401–414.